

# ***Passcert***

Higher Quality, better service!



# **Q&A**

***[Http://www.passcert.com](http://www.passcert.com)***

***We offer free update service for one year.***

**Exam** : **AP0-001**

**Title** : Acme Packet Certification  
Certification Exams Boot  
camp & Braindump

**Version** : DEMO

1.The Net-Net 4000 is the source and destination for all signaling messages and media streams coming into and leaving the provider's network. Which two of the following SIP functions does it provide?

- A.edge proxy
- B.registrar
- C.Back to Back User Agent
- D.media gateway

Answer:A C

2.Which two of the following statements about SIP response code handling on the Net-Net 4000 are TRUE?

- A.The Net-Net 4000 will originate a 403 Forbidden response when bandwidth allocated to a realm has been exhausted.
- B.The Net-Net 4000 cannot originate 3xx class redirect responses.
- C.The Net-Net 4000 egress realm selection may be affected by received third party 3xx class redirect responses
- D.The Net-Net 4000 can transmit a different SIP response code than it received.

Answer:C D

3.In an H.323 network, a \_\_\_\_\_ provides translation services and communication between dissimilar networks.

- A.gatekeeper
- B.gateway
- C.multipoint control unit
- D.codec

Answer:B

4.A steering pool defines \_\_\_\_\_.

- A.a range of IP addresses used to route media flows as they egress the box
- B.a range of IP addresses and a pool of ports Net-Net 4000 will use to declare itself as the destination for all subsequent media flows in a dialog
- C.an IP address and range of ports the Net-Net 4000 will use to declare itself as the destination for media flows in a session
- D.an IP address and port the Net-Net 4000 uses for steering media to the external media server

Answer:C

5.Which two of the following statements regarding SIP processing are FALSE?

- A.An initial INVITE will contain a From header tag and a To header tag as a globally unique identifier for the dialog.
- B.To avoid retransmissions, User Agents must forward received 100 Trying messages to their next hop.
- C.Calls Per Second are typically measured using a 7-10 message SIP call flow including call set-up and tear down.
- D.The combination of the To tag, From tag, and Call-ID completely defines a peer-to-peer SIP relationship and is referred to as a dialog.

Answer:A B

6.High availability (HA) nodes identify one another by their \_\_\_\_\_ names.

- A.Identifier
- B.Host
- C.mib-system-name

D.target

Answer:D

7.If upon examination of two configuration files you notice that the version number of the permanently saved configuration differs from the version number of the running configuration, it means that \_\_\_\_\_.

- A.the saved configuration file has been edited, but the done command was not issued
- B.the saved configuration file has been copied from flash into SDRAM using the save-config command
- C.the saved configuration file has been saved into flash, but the activate-config command has not been issued
- D.the saved configuration file was copied from flash into SDRAM using the activate-config command

Answer:C

8.Which one of the following statements about H.323 networks is FALSE?

- A.The collection of all terminals, gateways, and MCU managed by a single gatekeeper is known as an Autonomous System (AS).
- B.Gateways are not mandatory in an H.323 network.
- C.Gatekeepers are not mandatory in an H.323 network.
- D.Gateways translate call set-up messages and convert media formats.

Answer:A

9.The default baud rate for console connections to the Net-Net 4000 is \_\_\_\_\_.

- A.115200
- B.2400
- C.9600
- D.56600

Answer:A

10.In a high availability (HA) scenario, if peers boot simultaneously and their health scores are equivalent, which node automatically assumes the role of Active?

- A.The node that had the role of active last.
- B.The node that had the role of standby last.
- C.The node with the highest Wancom IP address.
- D.The node with the lowest Wancom IP address.

Answer:D

11.In a(n) \_\_\_\_\_ exchange, a Master Slave Determination message is an example of a type of message that might be exchanged during the media setup portion of the call.

- A.RAS
- B.ISDN
- C.H.245
- D.H.225

Answer:C

12.When two associated H323 stacks in different realms have the gatekeeper parameter defined, which one of the following statements is TRUE?

- A.The Net-Net 4000 will proxy LRQ and LCF messages from one gatekeeper to the other and the TCP connection for H.225.0 will be established afterwards.
- B.The Net-Net 4000 will respond locally to the LRQ with a LCF, and upon receiving the SETUP on the ingress leg, will open the TCP connection on the egress leg to send the SETUP.

- C.It is not possible to have two associated H323 stacks when both have gatekeepers defined.
- D.Registrations will be forwarded from one Gatekeeper to the other using unique RRQ messages.

Answer:A

13.Best current practice for the initial turn-up of a secondary node in a highly available (HA) pair calls for the acquire-config command targeting the \_\_\_\_\_interface on the primary node.

- A.Wancom0
- B.Wancom1
- C.Wancom2
- D.Wancom3

Answer:A

14.To view an existing multiple instance element configuration you can go to the correct branch of the configuration tree and \_\_\_\_\_.

- A.select the element and then issue the show command
- B.enter the name of the element and then issue the show command
- C.type show and select from the displayed list
- D.type show

Answer:A

15.When associating network interfaces to a physical interface on the Net-Net 4000, the \_\_\_\_\_ fields must contain the same unique ID.

- A.sub-port-id
- B.name
- C.unique-id
- D.identifier

Answer:B